Product Service

CERTIFICATE

No. Z1 048273 0009 Rev. 00

Holder of Certificate: **Meltem Wärmerückgewinnung GmbH & Co. KG**
Am Hartholz 4
82239 Alling
GERMANY

Certification Mark:

Product: **Ventilation Equipment**
Decentral ventilation for dwellings with heat recovery

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 028-713143716-000

Valid until: 2024-03-24

Date, 2019-03-27

(Guido Kuttler)

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV SÜD ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

TÜV SÜD ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

Product Service

CERTIFICATE

No. Z1 048273 0009 Rev. 00

Model(s):

M-WRG-II P, M-WRG-II P-F , M-WRG-II P-FC , M-WRG-II P-T, M-WRG-II P-T-F , M-WRG-II P-T-FC , M-WRG-II P-M , M-WRG-II P-M-F , M-WRG-II P-M-FC, M-WRG-II P-S 485 , M-WRG-II P-S 485-F, M-WRG-II P-S 485-FC, M-WRG-II E , M-WRG-II E-F , M-WRG-II E-FC , M-WRG-II E-T, M-WRG-II E-T-F , M-WRG-II E-T-FC , M-WRG-II E-M , M-WRG-II E-M-F, M-WRG-II E-M-FC , M-WRG-II E-S 485 , M-WRG-II E-S 485-F , M-WRG-II E-S 485-FC, M-WRG-II M-U²

Parameters:

Model	Rated power	Rated voltage	Rated frequency	Degree of protection	Protection class
M-WRG-II P	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-T	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-T-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-T-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-M	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-M-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-M-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-S 485	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-S 485-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II P-S 485-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-T	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-T-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-T-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-M	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-M-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-M-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-S 485	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-S 485-F	max. 53W	230V	50Hz	IPX4	II
M-WRG-II E-S 485-FC	max. 53W	230V	50Hz	IPX4	II
M-WRG-II M-U²	--	--	--	IPX5	--

Tested according to:

EN 60335-2-65:2003/A11:2012
EN 60335-1:2012/A13:2017
EN 62233:2008

Production Facility(ies):

011675

TÜV SÜD Product Service GmbH • Certification Body • Ridlerstraße 65 • 80339 Munich • Germany

TÜV®